

# F30-2



## F30-2

### Flat suction cup with cleats

- Suitable for flat objects.
- Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.



#### Lifting forces & Technical data

Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume	Min. curve radius	Max. vertical movement	Weight rubber part
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa	cm <sup>3</sup>	mm	mm	g
12.0	25	31	11.0	16.0	20.0	2.0	25	2.0	2.2

#### Material specifications


Material	Colour	Hardness °Shore A	Temperature range °C
Chloroprene, CR	Black	50	-40–110
Silicone, SIL	Red	50	-40–200

#### Material resistance


Material	Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Chloroprene, CR	Excellent	Fair	Good	Good	Fair	Poor	Good	Good
Silicone, SIL	Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent

## Ordering information

Complete suction cups		Art. No.
A	Suction cup F30-2 Chloroprene, M5 female	0101325
A	Suction cup F30-2 Chloroprene, M5 female, with dual flow control valve	0101331
B	Suction cup F30-2 Chloroprene, G1/8" male, with mesh filter	0101326
B	Suction cup F30-2 Chloroprene, G1/8" male, with mesh filter and dual flow control valve	0101332
C	Suction cup F30-2 Chloroprene, G1/8" male/M5 female, with mesh filter	0101330
C	Suction cup F30-2 Chloroprene, G1/8" male/M5 female, with dual flow control valve	0101334
E	Suction cup F30-2 Chloroprene, G1/8" male/M5 female PA	0109846
F	Suction cup F30-2 Chloroprene, G1/8" male/M5 female, with cone valve	3250039
D	Suction cup F30-2 Chloroprene, 5xM5 female	0101329
A	Suction cup F30-2 Silicone, M5 female	0101341
B	Suction cup F30-2 Silicone, G1/8" male, with mesh filter	0101342
B	Suction cup F30-2 Silicone, G1/8" male, with mesh filter and dual flow control valve	0101348
C	Suction cup F30-2 Silicone, G1/8" male/M5 female, with mesh filter	0101346
C	Suction cup F30-2 Silicone, G1/8" male/M5 female, with dual flow control valve	0101350
D	Suction cup F30-2 Silicone, 5xM5 female	0101345
E	Suction cup F30-2 Silicone, G1/8" male/M5 female PA	0110344
F	Suction cup F30-2 Silicone, G1/8" male/M5 female, with cone valve	3250039S



Rubber parts	Art. No.
Suction cup F30-2 Chloroprene	0101133
Suction cup F30-2 Chloroprene, for fitting with cone valve	3150239
Suction cup F30-2 Silicone	0101134



Fittings	Art. No.
Fitting M5 female	3250003
Fitting M5 female, with dual flow control valve	3251001
Fitting G1/8" male, with mesh filter	3250085
Fitting G1/8" male, with mesh filter and dual flow control valve	3251002
Fitting G1/8" male/M5 female, with mesh filter	0101152
Fitting G1/8" male/M5 female, with dual flow control valve	3251004

Fitting G1/8" male/M5 female, with cone valve	0101155
Fitting 5xM5 female	0100260
Fitting 5xM5 female, with dual flow control valve	3251005
Fitting G1/8" male/M5 female, PA	3150196

Spare Part	Material	Temperature range °C	Art. No.
Cone valve for F30-2	Al/SS/NBR	-40–110	3150055