

# U15-3



## U15-3

### Universal suction cup

- Wide temperature range (-76°F to +392°F)
- Enforced lip

#### Lifting forces & Technical data

Outer Dia in	Lifting force vertical to the surface, lbf, at vacuum level			Lifting force parallel to the surface, lbf, at vacuum level			Volume in <sup>3</sup>	Min. curve radius in	Max. vertical movement in	Weight rubber part oz
	6 -inHg	18 -inHg	27 -inHg	6 -inHg	18 -inHg	27 -inHg				
0.65	0.79	1.89	2.47	0.79	1.21	1.33	0.03	0.31	0.06	0.02

#### Material specifications

Material	Color	Hardness °Shore A	Temperature range °F
Silicone, SIL	Red	40	-40-392

#### Material resistance

Material	Wear resistance	Oil	Weather & Ozone	Hydrolysis	Gasoline	Concentrated acids	Alcohol	Oxidation
Silicone, SIL	Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent


## Ordering information

### Description

Suction cup U15-3 Silicone, M5 male

### Part No.

U15-3.20.01AC




### Description

Suction cup U15-3 Silicone

### Part No.

U15-3.20



### Fittings

Fitting M5 male, 10-15

### Part No.

01AC